

1

AD-A205 501

PORT DOCUMENTATION PAGE

4. PERFORMING ORGANIZATION REPORT NUMBER(S)		1b. RESTRICTIVE MARKINGS	
6a. NAME OF PERFORMING ORGANIZATION Naval Ocean Systems Center		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.	
6b. ADDRESS (City, State and ZIP Code) San Diego, CA 92152-5000		5. MONITORING ORGANIZATION REPORT NUMBER(S)	
7a. NAME OF MONITORING ORGANIZATION Naval Ocean Systems Center		7b. ADDRESS (City, State and ZIP Code) San Diego, CA 92152-5000	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION Defense Advance Research Projects Agency		8b. OFFICE SYMBOL (if applicable) NOSC	
8c. ADDRESS (City, State and ZIP Code) 1400 Wilson Blvd. Arlington, VA 22209		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
10. SOURCE OF FUNDING NUMBERS		11. TITLE (include Security Classification)	
PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	AGENCY ACCESSION NO.
0602301E	EE87		DN388 650
EIGHT CHANNEL 5 Gb/s OPTOELECTRONIC TDM			
12. PERSONAL AUTHOR(S) D. J. Albares, C. T. Chang, T. R. Ogden, G. A. Garcia, M. N. McLandrich, R. E. Reedy			
13a. TYPE OF REPORT Presentation/speech	13b. TIME COVERED FROM Oct 1988 TO Oct 1988	14. DATE OF REPORT (Year, Month, Day) February 1989	15. PAGE COUNT
16. SUPPLEMENTARY NOTATION			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	
			GAAS integration
			silicon
			optics
19. ABSTRACT (Continue on reverse if necessary and identify by block number)			
<p>An 8:1, 5 Gb/s, time division multiplexer has been implemented using optoelectronic or metal-semiconductor-metal switches for sampling. The device was fabricated on InP and the switches activated via optical fiber delay lines by pulses from a GaAlAs laser diode array. This device concept is applicable to chip and to board level computer multiplexing.</p> <p>Time division multiplexing (TDM), serializing parallel data for high speed transmission, is an important element in most concepts and implementations in computer networking as well as other areas of communications. An optoelectronic TDM (OE-TDM) approach[1] is advantageous in speed, power, and signal-control isolation. It was conceived initially to offer serial transmission off VLSI chips and recently has shown promise as a stand alone multiplexing technique. We report an improved multiplexer in InP giving an 8:1 multiplex ratio, a 26 dB signal-to-noise ratio, and a 5 Gb/s serial data rate while using a realistic parallel data level of 2 volts instead of the earlier 15 V[1].</p> <p>The OE-TDM multiplexer concept is shown schematically in Figure 1, where the digital word, e.g. 4 bits are shown, is conducted on parallel metallic lines containing the EO switches. The output from each switch fans into a single high-speed transmission line. The switches are closed (low resistance) sequentially by laser light pulses transmitted with proper delays through optical fibers, serializing the word. The single transmission line carries the serial electrical data to a matched line for further transmission, possibly conversion to fiber optics, and eventual demultiplexing.</p> <p>The multiplexer featured 8 input lines with bonding pads, 60X60 micron interdigital electrodes with 2 micron fingers and gaps and a 50-ohm coplanar transmission line output. The devices were fabricated by standard semiconductor techniques on semi-insulating InP. A 10-laser diode array was coupled to a 1:8 fiber coupler whose 8 output fibers were trimmed for the proper relative delays, cemented to an etched Si v-groove chip and aligned to the switches. The laser pulses were below 50 ps FWHM and approximately 20 mW peak power at the switches. They are shown detected by a fast PIN photodiode and by an InP switch in Figures 2a and 2b.</p>			
(Continued on reverse side)			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT		21. ABSTRACT SECURITY CLASSIFICATION	
<input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS		UNCLASSIFIED	
22a. NAME OF RESPONSIBLE PERSON D. J. Albares		22b. TELEPHONE (include Area Code) (619) 553-3907	22c. OFFICE SYMBOL Code 553

DTIC
SELECTED
16 MAR 1989

89 3 16 057

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

19. ABSTRACT (Continued)

The experimental demonstration used dc voltages applied to the 8 lines with the laser pulser operating at 100 Mhz repetition frequency. The output line was coupled to a 50 ohm coaxial cable which transmitted the signals to a sampling oscilloscope. A serial bit stream from an InP multiplexer is shown in Figure 3 where we estimate a data rate of 5 Gb/s and a S/N of 26 dB.

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

Presented at MILCOM 88, 23 - 26 Oct 1988, San Diego, CA.

D. J. Albares, C. T. Chang, T. R. Ogden, M. N. McLandrich, G. A. Garcia and R. E. Reedy

Naval Ocean Systems Center
San Diego, California 92152-5000

ABSTRACT

An 8:1, 5 Gb/s, time division multiplexer has been implemented using optoelectronic or metal-semiconductor-metal switches for sampling. The device was fabricated on InP and the switches activated via optical fiber delay lines by pulses from a GaAlAs laser diode array. This device concept is applicable to chip and to board level computer multiplexing.

Time division multiplexing (TDM), serializing parallel data for high speed transmission, is an important element in most concepts and implementations in computer networking as well as other areas of communications. An optoelectronic TDM (OE-TDM) approach[1] is advantageous in speed, power, and signal-control isolation. It was conceived initially to offer serial transmission off VLSI chips and recently has shown promise as a stand alone multiplexing technique. We report an improved multiplexer in InP giving an 8:1 multiplex ratio, a 26 dB signal-to-noise ratio, and a 5 Gb/s serial data rate while using a realistic parallel data level of 2 volts instead of the earlier 15 V[1].

The OE-TDM multiplexer concept is shown schematically in Figure 1, where the digital word, e.g. 4 bits are shown, is conducted on parallel metallic lines containing the EO switches. The output from each switch fans into a single high-speed transmission line. The switches are closed (low resistance) sequentially by laser light pulses transmitted with proper delays through optical fibers, serializing the word. The single transmission line carries the serial electrical data to a matched line for further transmission, possibly conversion to fiber optics, and eventual demultiplexing.

The multiplexer featured 8 input lines with bonding pads, 60X60 micron interdigital electrodes with 2 micron fingers and gaps and a 50-ohm coplanar transmission line output. The devices were fabricated by standard semiconductor techniques on semi-insulating InP. A 10-laser diode array was coupled to a 1:8 fiber coupler whose 8 output fibers were trimmed for the proper relative delays, cemented to an etched Si v-groove chip and aligned to the switches. The laser pulses were below 50 ps FWHM and approximately 20 mW peak power at the switches. They are shown detected by a fast PIN photodiode and by an InP switch in Figures 2a and 2b.

The experimental demonstration used dc voltages applied to the 8 lines with the laser pulser operating at 100 Mhz repetition frequency. The output line was coupled to a 50 ohm coaxial cable which transmitted the signals to a sampling oscilloscope. A serial bit stream from an InP multiplexer is shown in Figure 3 where we estimate a data rate of 5 Gb/s and a S/N of 26 dB.

2. REFERENCES

1. D. J. Albares et al, "Optoelectronic Time Division Multiplexing," Electronics Lett., 23(7), 327-328 (1985).




Figure 1. Schematic of OE Multiplexer




Figure 2a. Laser pulse from diode array detected by PIN diode.




Figure 2b. Electrical pulse from InP switch with 2V bias.




Figure 3. 8:1 Multiplexer output with 2V bias.